





The SetFast bolt is the first telescopic closet bolt that requires "No Cutting" or "Break Off". SetFast bolts install like a standard closet bolt but adjust like no other. Just tighten the nut and watch the bolt get shorter with every turn.

SetFast bolts are a real time saver that simplifies both toilet installation and removal. Sold in pairs, 2 bolts per pack.

## Features:

- Professional grade 5/16" solid brass with stainless steel washers
- No Cutting or Break-off
- No Spinning
- No Tipping
- Self Adjusting Length (42443)
- Adjustable Length (53990). Great for installations where the closet flange is below the finished floor.

PRODUCT	DESCRIPTION	MODEL	UNITS/CASE	
	SetFast Self Adjusting Closet Bolt			
42443	Standard Length – 5/16" x 2-1/4"	42443	100	
	SetFast Adjustable Closet Bolt			
53990	Extended Length – 5/16" x 3"	53990	50	

## **Standard Length** Item: 42443 Self Adjusting Size 5/16" x 2-1/4" down to 1-1/2"

**XT Length** ltem: 53990 Adjustable Size 5/16" x 3"



**Turning the brass nut** forces the bolt to turn once it hits the unique white dot "thread locker". This action is what makes the bolt a self-adjusting tool.

1662 Stand

Flat sides on the bolt ridge and body prevent the bolt from spinning.



Jam-Bar

**SEE BACK SIDE** 











## Jam+Bar Toilet Bolt Lock Wrench

Toilet bowl removal can be difficult if the bolt(s) are corroded or have damaged ends. Forcing the nut can often cause the bolt to break free and spin. Because space is limited, holding back on the bolt using conventional tools can be difficult.

The "Jam-Bar" is a thin bladed wrench designed to fit into tight spaces. The patented fork-like blade and serrated teeth grip and hold the bolt. The more the bolt tries to spin, the tighter the grip. Works on both 1/4" and 5/16 bolts.

## Features:

- Simplifies toilet and tank removal
- Quality tool steel
- Grips 1/4" to 5/16" threaded bolts







PRODUCT	DESCRIPTION	MODEL	UNITS/CASE
53991	Jam-Bar Toilet Bolt Lock Wrench	53991	8