

## Weld-On® White Seal™ Plus

Version number: 2.0  
Replaces version of: 2023-08-30 (1)

Revision: 2023-10-27

### SECTION 1: Identification

#### 1.1 Product identifier

Trade name **Weld-On® White Seal™ Plus**  
Product category/ies Pipe Thread Sealant

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses sealant

#### 1.3 Details of the supplier of the safety data sheet

Weld-On  
17109 S. Main  
Gardena CA 90248-3127  
United States

Telephone: 1-310-898-3300  
e-mail: EHSInfo@ipscorp.com  
Website: www.weldon.com

#### 1.4 Emergency telephone number

Emergency information service 24 Hours - CHEMTEL: (800) 255-3924; International (813) 248-0585

### SECTION 2: Hazard(s) identification

#### 2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Hazard class	Category
acute toxicity (inhal.)	4
skin corrosion/irritation	2
serious eye damage/eye irritation	2B
specific target organ toxicity - single exposure (respiratory tract irritation)	3

For full text of abbreviations: see SECTION 16.

#### 2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word warning

- Pictograms

GHS07



- Hazard statements

H315+H320 Causes skin and eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Weld-On® White Seal™ Plus

Version number: 2.0  
Replaces version of: 2023-08-30 (1)

Revision: 2023-10-27

### - Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves.
- P302+P352 If on skin: Wash with plenty of water.
- P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 Call a poison center/doctor if you feel unwell.
- P321 Specific treatment (see on this label).
- P362 Take off contaminated clothing and wash before reuse.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P501 Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling Distillates (petroleum), hydrotreated light paraffinic, Talc

### 2.3 Other hazards

Special danger of slipping by leaking/spilling product.

Hazards not otherwise classified

Harmful to aquatic life with long lasting effects (GHS category 3: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance in a concentration of  $\geq 0.1\%$ .

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of  $\geq 0.1\%$ .

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture)

### 3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
Distillates (petroleum), hydro-treated light paraffinic	CAS No 64742-55-8	25 - < 50	Acute Tox. 4 / H332
Talc	CAS No 14807-96-6	10 - < 25	Acute Tox. 4 / H332
Crystalline silica (quartz)	CAS No 14808-60-7	10 - < 25	Carc. 1A / H350

For full text of abbreviations: see SECTION 16.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Weld-On® White Seal™ Plus

Version number: 2.0  
Replaces version of: 2023-08-30 (1)

Revision: 2023-10-27

### SECTION 4: First-aid measures

#### 4.1 Description of first-aid measures

##### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

##### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

##### Following skin contact

Wash with plenty of soap and water.

##### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

##### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

#### 4.3 Indication of any immediate medical attention and special treatment needed

none

### SECTION 5: Fire-fighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO<sub>2</sub>)

##### Unsuitable extinguishing media

Water jet

#### 5.2 Special hazards arising from the substance or mixture

##### Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

##### Flash point

>450 °F

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## Weld-On® White Seal™ Plus

Version number: 2.0  
Replaces version of: 2023-08-30 (1)

Revision: 2023-10-27

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

#### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities

- Ventilation requirements

Keep any substance that emits harmful vapors or gases in a place that allows these to be permanently extracted.

#### 7.3 Specific end use(s)

See section 16 for a general overview.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Weld-On® White Seal™ Plus

Version number: 2.0  
Replaces version of: 2023-08-30 (1)

Revision: 2023-10-27

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
US	zinc oxide	1314-13-2	REL		5 (10 h)				15	dust	NIOSH REL
US	zinc oxide	1314-13-2	PEL (CA)		5		10			fume	Cal/ OSHA PEL
US	zinc oxide	1314-13-2	REL		5 (10 h)		10			fume	NIOSH REL
US	zinc oxide	1314-13-2	PEL		5					fume	29 CFR 1910.1000
US	zinc oxide	1314-13-2	PEL		15					i, dust	29 CFR 1910.1000
US	zinc oxide	1314-13-2	TLV®		2		10			r	ACGIH® 2023
US	zinc oxide	1314-13-2	PEL		5					r, dust	29 CFR 1910.1000
US	talc	14807-96-6	PEL (CA)	1						+asb, fib/cm <sup>3</sup>	Cal/ OSHA PEL
US	talc	14807-96-6	TLV®		0.1					fib/cm <sup>3</sup> , +asb, CA-10	ACGIH® 2023
US	talc	14807-96-6	PEL		0.1		1 (30 min)			no_asb, fib/ml	29 CFR 1910.1000
US	talc	14807-96-6	PEL (CA)		2					no_asb, r, less1silica	Cal/ OSHA PEL
US	talc	14807-96-6	PEL	706						partml, noAsb, less1Sil, r	29 CFR 1910.1000
US	talc	14807-96-6	REL		2 (10 h)					r, less1silica, no_asb	NIOSH REL
US	talc	14807-96-6	TLV®		2					r, noAsb, less1Sil	ACGIH® 2023



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Weld-On® White Seal™ Plus

Version number: 2.0  
Replaces version of: 2023-08-30 (1)

Revision: 2023-10-27

### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Notation	Source
US	quartz	14808-60-7	PEL (CA)		0.05					r	Cal/ OSHA PEL
US	silica, crystalline - quartz	14808-60-7	PEL		0.05					r	29 CFR 1910.1000
US	silica, crystalline - quartz	14808-60-7	REL		0.05 (10 h)					r, appx-A	NIOSH REL
US	Polytetrafluoroethylene, decomposition products	9002-84-0	PEL (CA)							PTFE-decomp	Cal/ OSHA PEL

#### Notation

- +asb containing asbestos fibers
- appx-A NIOSH Potential Occupational Carcinogen (Appendix A)
- CA-10 Respirable fibers: length > 5µm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450 times magnification (4-mm objective), using phase-contrast illumination.
- Ceiling-C ceiling value is a limit value above which exposure should not occur
- dust as dust
- fib/cm³ fibers/cm³
- fib/ml fibers/ml
- fume as fume
- i inhalable fraction
- less1silica with less than 1 % free crystalline silica
- no\_asb containing no asbestos fibers
- noAsb\_less1S contains no asbestos and less than 1% free crystalline silica
- il
- partml particles/ml
- PTFE-decomp Thermal decomposition of the fluorocarbon chain in air leads to the formation of oxidized products containing carbon, fluorine and oxygen. An index of exposure to these products is possible through their alkaline hydrolysis followed by a quantitative determination of fluoride content. No particular concentration limit is specified pending evaluation of the toxicity of the products but concentrations should be kept below the sensitivity of the analytical method
- r respirable fraction
- STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
- TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

### Relevant DNELs of components

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Talc	14807-96-6	DNEL	2.16 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
Talc	14807-96-6	DNEL	2.16 mg/m³	human, inhalatory	worker (industry)	acute - systemic effects
Talc	14807-96-6	DNEL	3.6 mg/m³	human, inhalatory	worker (industry)	chronic - local effects
Talc	14807-96-6	DNEL	3.6 mg/m³	human, inhalatory	worker (industry)	acute - local effects
Talc	14807-96-6	DNEL	43.2 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

## Weld-On® White Seal™ Plus

Version number: 2.0  
Replaces version of: 2023-08-30 (1)

Revision: 2023-10-27

Relevant PNECs of components						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
Talc	14807-96-6	PNEC	598 mg/l	aquatic organisms	freshwater	short-term (single instance)
Talc	14807-96-6	PNEC	141.3 mg/l	aquatic organisms	marine water	short-term (single instance)
Talc	14807-96-6	PNEC	31.33 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Talc	14807-96-6	PNEC	3.13 mg/kg	aquatic organisms	marine sediment	short-term (single instance)

### 8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state	liquid (paste)
Color	white
Particle	not relevant (liquid)



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Weld-On® White Seal™ Plus

Version number: 2.0  
Replaces version of: 2023-08-30 (1)

Revision: 2023-10-27

Odor	characteristic
------	----------------

### Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	≥207 °C at 101.3 kPa
Flash point	>450 °F
Flash point	>450 °F
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	<0.1 hPa at 20 °C
Density	1.28 g/cm <sup>3</sup> at 80 °F
Vapor density	this information is not available

### Solubility(ies)

- Water solubility	0 mg/cm <sup>3</sup>
--------------------	----------------------

### Partition coefficient

- n-octanol/water (log KOW)	this information is not available
-----------------------------	-----------------------------------

Auto-ignition temperature	not determined
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

### 9.2 Other information

VOC content	When applied as directed, per SCAQMD Rule 1168, Test Method 316A, VOC content is:
-------------	---





# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Weld-On® White Seal™ Plus

Version number: 2.0  
Replaces version of: 2023-08-30 (1)

Revision: 2023-10-27

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

#### 10.2 Chemical stability

See below "Conditions to avoid".

#### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

#### 10.5 Incompatible materials

Oxidizers

#### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

##### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

##### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

##### Acute toxicity

Harmful if inhaled.

##### Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	inhalation: vapor	11 mg/l/4h
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	inhalation: dust/mist	2.18 mg/l/4h
Talc	14807-96-6	inhalation: dust/mist	>2.1 mg/l/4h

##### Skin corrosion/irritation

Causes skin irritation.

##### Serious eye damage/eye irritation

Causes eye irritation.

##### Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

## Weld-On® White Seal™ Plus

Version number: 2.0  
Replaces version of: 2023-08-30 (1)

Revision: 2023-10-27

### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

### Carcinogenicity

Shall not be classified as carcinogenic.

#### IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
Talc	14807-96-6	3	
Talc	14807-96-6	2B	
Crystalline silica (quartz)	14808-60-7	1	

#### Legend

- 1 Carcinogenic to humans
- 2B Possibly carcinogenic to humans
- 3 Not classifiable as to carcinogenicity in humans

### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

### Specific target organ toxicity - single exposure

May cause respiratory irritation.

### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

## SECTION 12: Ecological information

### 12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	LL50	>100 mg/l	fish	96 h
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	EL50	>10,000 mg/l	aquatic invertebrates	24 h
Talc	14807-96-6	LC50	89,581 mg/l	fish	96 h
Talc	14807-96-6	EC50	7,203 mg/l	algae	96 h

### 12.2 Persistence and degradability

Data are not available.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Weld-On® White Seal™ Plus

Version number: 2.0  
Replaces version of: 2023-08-30 (1)

Revision: 2023-10-27

### 12.3 Bioaccumulative potential

Data are not available.

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of  $\geq 0.1\%$ .

### 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of  $\geq 0.1\%$ .

### 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

## SECTION 14: Transport information

14.1	UN number	not subject to transport regulations
14.2	UN proper shipping name	not relevant
14.3	Transport hazard class(es)	none
14.4	Packing group	not assigned
14.5	Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations
14.6	Special precautions for user	
	There is no additional information.	
14.7	Transport in bulk according to IMO instruments	
	The cargo is not intended to be carried in bulk.	

### Information for each of the UN Model Regulations

#### Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Not subject to transport regulations.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Weld-On® White Seal™ Plus

Version number: 2.0  
Replaces version of: 2023-08-30 (1)

Revision: 2023-10-27

### International Maritime Dangerous Goods Code (IMDG) - Additional information

Not subject to IMDG.

### International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Not subject to ICAO-IATA.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations specific for the product in question

#### National regulations (United States)

##### Toxic Substance Control Act (TSCA)

all ingredients are listed as ACTIVE

##### Superfund Amendment and Reauthorization Act (SARA TITLE III )

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

##### Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

none of the ingredients are listed

##### Clean Air Act

none of the ingredients are listed

##### Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8		EC Annex VI CMRs - Cat. 1B
Crystalline silica (quartz)	14808-60-7		IARC Carcinogens - 1

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
Crystalline silica (quartz)		1095			1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
Talc	14807-96-6	A, O	fiber
Talc	14807-96-6	A, R, *	fiber
Crystalline silica (quartz)		A, *	

#### Legend

\* Substances which are regulated by OSHA as carcinogens; have been categorized by the ACGIH as either "human carcinogens" or "suspect of carcinogenic potential for man"; have been evaluated by the International Agency for Research on Cancer (IARC) and found to be carcinogens or potential carcinogens; or have been listed as a carcinogen or potential carcinogen in the Annual Report on Carcinogens published by the National Toxicology Program (NTP).



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Weld-On® White Seal™ Plus

Version number: 2.0  
Replaces version of: 2023-08-30 (1)

Revision: 2023-10-27

### Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division
- R International Agency for Research on Cancer (IARC) Monographs on the Evaluation of the Carcinogenic Risks to Humans; Overall Evaluations of Carcinogenicity: An Updating of IARC Monographs Volumes 1 to 42, Supplement 7 (1987). Available from: WHO Publications Centre USA

### - Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
Talc	14807-96-6	containing no asbestos fibers	
Talc	14807-96-6	containing asbestos fibers	CA
Crystalline silica (quartz)	14808-60-7		CA

### Legend

- CA Carcinogenic

### - Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
TALC (MG3H2(SIO3)4)	14807-96-6	
QUARTZ (SIO2)	14808-60-7	

### - Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
Talc	14807-96-6	T
Crystalline silica (quartz)	14808-60-7	T
Crystalline silica (quartz)	14808-60-7	T

### Legend

- T Toxicity (ACGIH®)

### Industry or sector specific available guidance(s)

#### NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Weld-On® White Seal™ Plus

Version number: 2.0  
Replaces version of: 2023-08-30 (1)

Revision: 2023-10-27

Category	Rating	Description
Personal protection	-	

### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

### National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)

#### Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

## Weld-On® White Seal™ Plus

Version number: 2.0  
Replaces version of: 2023-08-30 (1)

Revision: 2023-10-27

### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information, including date of preparation or last revision

#### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.3		Hazards not otherwise classified: change in the listing (table)	yes
2.3	Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$ .	Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$ .	yes
7.2	- Packaging compatibilities: Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.		yes
9.1	Solubility(ies): not determined	Solubility(ies)	yes
9.1		Water solubility: $0 \text{ mg/cm}^3$	yes
12.1	Toxicity: Toxic to aquatic life with long lasting effects.	Toxicity: Harmful to aquatic life with long lasting effects.	yes
12.6	Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$ .	Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$ .	yes
13.1	Waste treatment of containers/packages: Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.	Waste treatment of containers/packages: Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.	yes
14.1	UN number	UN number: not subject to transport regulations	yes
14.1	DOT: UN 3082		yes
14.1	IMDG-Code: UN 3082		yes
14.1	ICAO-TI: UN 3082		yes
14.2	DOT: Environmentally hazardous substance, liquid, n.o.s.		yes
14.2	IMDG-Code: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.		yes
14.2	ICAO-TI: Environmentally hazardous substance, liquid, n.o.s.		yes
14.2	Technical name (hazardous ingredients): zinc oxide		yes



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Weld-On® White Seal™ Plus

Version number: 2.0  
Replaces version of: 2023-08-30 (1)

Revision: 2023-10-27

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
14.3	DOT: 9		yes
14.3	IMDG-Code: 9		yes
14.3	ICAO-TI: 9		yes
14.4	DOT: III		yes
14.4	IMDG-Code: III		yes
14.4	ICAO-TI: III		yes
14.5	Environmentally hazardous substance (aquatic environment): zinc oxide		yes
14.7	Particulars in the shipper's declaration: UN3082, Environmentally hazardous substance, liquid, n.o.s., (contains: zinc oxide), 9, III		yes
14.7	Danger label(s): 9, fish and tree		yes
14.7		Danger label(s): change in the listing (table)	yes
14.7	Environmental hazards: yes (hazardous to the aquatic environment)		yes
14.7	Special provisions (SP): 8, 146, 173, 335, 441, IB3, T4, TP1, TP29		yes
14.7	ERG No: 171		yes
14.7	Marine pollutant: yes (hazardous to the aquatic environment) (zinc oxide)		yes
14.7	Danger label(s): 9, fish and tree		yes
14.7		Danger label(s): change in the listing (table)	yes
14.7	Special provisions (SP): 274, 335, 969		yes
14.7	Excepted quantities (EQ): E1		yes
14.7	Limited quantities (LQ): 5 L		yes
14.7	EmS: F-A, S-F		yes





# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Weld-On® White Seal™ Plus

Version number: 2.0  
Replaces version of: 2023-08-30 (1)

Revision: 2023-10-27

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
14.7	Stowage category: A		yes
14.7	Environmental hazards: yes (hazardous to the aquatic environment)		yes
14.7	Danger label(s): 9, fish and tree		yes
14.7		Danger label(s): change in the listing (table)	yes
14.7	Special provisions (SP): A97, A158, A197, A215		yes
14.7	Excepted quantities (EQ): E1		yes
14.7	Limited quantities (LQ): 30 kg		yes
14.2	UN proper shipping name	UN proper shipping name: not relevant	yes
14.3	Transport hazard class(es)	Transport hazard class(es): none	yes
14.4	Packing group	Packing group: not assigned	yes
14.5	Environmental hazards: hazardous to the aquatic environment	Environmental hazards: non-environmentally hazardous acc. to the dangerous goods regulations	yes
14.7	Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information	Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information: Not subject to transport regulations.	yes
14.7	International Maritime Dangerous Goods Code (IMDG) - Additional information	International Maritime Dangerous Goods Code (IMDG) - Additional information: Not subject to IMDG.	yes
14.7	International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information	International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information: Not subject to ICAO-IATA.	yes

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2023	From ACGIH®, 2023 TLVs® and BEIs® Book. Copyright 2023. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: <a href="http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement">http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement</a>
Acute Tox.	Acute toxicity



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Weld-On® White Seal™ Plus

Version number: 2.0  
Replaces version of: 2023-08-30 (1)

Revision: 2023-10-27

Abbr.	Descriptions of used abbreviations
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LHS	Lower hazard substance
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Weld-On® White Seal™ Plus

Version number: 2.0  
Replaces version of: 2023-08-30 (1)

Revision: 2023-10-27

Abbr.	Descriptions of used abbreviations
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
STEL	Short-term exposure limit
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

### Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H332	Harmful if inhaled.
H350	May cause cancer.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.