


# Multi-Size 3-8 Flashing

Introducing our newest roofing solution designed specifically for shingle applications to ensure long-lasting seals around DWV (drain, waste, and vent) roof penetrations. This product accommodates pipe sizes from 3 to 8 inches, providing a secure, watertight seal that protects against the elements. Built with a durable EPDM boot for optimal sealing performance and an oversized aluminum base that provides maximum coverage.



## Features

- 3"–8" pipe sizes
- Sleeve flexibility absorbs vibration and pipe movement caused by expansion/contraction
- Made of EPDM which are compounded specifically for maximum resistance to weathering due to ozone and ultraviolet light
- Easy on-site customization with pull tab design can accommodate all normal installations
- 20° pitch to accommodate 12/12 roof pitch
- Large footprint 22 gauge dead soft aluminum base
- EPDM is lab tested and certified: IAPMO PS64-2012ea1 

## Installation

1. Identify size needed.
2. Use "as is" for 3".
3. Pull tear out tab with pliers as pictured for other sizes.
4. Ensure there is a clean surface on pipe for boot to seal against.
5. Push boot over DWV pipe and slide flashing down to roof decking.



PROPERTY	ASTM TEST METHOD	CONDITION	RESULT
Low Temp Brittleness	D2137	-58°F / 50°C	Pass
High Temp Brittleness	D2137	302°F / 150°C	Pass
UV Resistance	G154	< 50% loss in tear strength and elongation after 2,000 Hr cycle test.	Pass
Ozone Resistance	D1149	7 Days @ 100pphm	No Cracks, Pass
Water Absorption	D471	2 Days @ 158°F < 5%	Pass
Working High Temperature	Intermittent	275°F / 135°C	Pass
Working High Temperature	Continuous	212°F / 100°C	Pass

PRODUCT	DESCRIPTION	PIPE SIZE	BASE SIZE	MODEL	UNITS/CASE
81499	Multi-Size 3-8 Aluminum Base Flashing	3"-8"	20" x 24"	DSALUF38	10